



iBOD-S Tiered Drive Enclosure



iBOD-S 4U 48 Drive High Density Enclosure

Key Features

- 48 Drive High Density Enclosure in 4U
 - Universal backplane supports SAS/ SATA
 - Front Accessible Hot Swap Carriers
 - Dual Channel SAS
 - Single channel SATA
 - Optional Dual Channel SATA
- 48 Gb Host Bandwidth Across Dual Expanders
 - Flexible Expander Connectivity
 - 2x wide SAS ports (12Gbit/sec) channels OR
 - 1x wide SAS (12Gbit/sec) + 4x single (3Gbit/sec) OR
 - 8x single SAS (3Gbit/sec) channels
- Cool By Design™
 - 90% Efficient Single Rail PSU
 - Conversion at Point of Load Power
 - Software Controlled Regulation of Variable Speed Fans
 - Low Heat Dissipation/ BTU Rating
- Compatible with leading Fibre Channel, iSCSI and SAS Head Ends, RAID Controllers and Storage Servers
- Cableless Design for Maximum Reliability
- Hot Swap Integrated Power Supplies and Fans
 - N+1 Single Rail High Efficiency PSU
 - Low Noise Auto-regulating Fans
 - Integrated I2C monitor of Voltage, Current, Temperature, Fan Speed and AC-Fail
 - I2C Monitor is independent of AC Supply
- Compact 24" Depth
- High Quality
 - ISO 9000 Design and Manufacture
 - ROHS compliant
- Ethernet & Serial Management Ports
- Tri-Color LED Indicators

The MPSTOR iBOD-S48 is the first in a new family of high-density intelligent tiered storage enclosures designed for OEM and integrators developing enterprise storage solutions. The iBOD-S48 is designed to provide a high-density 48-drive enclosure in a 4U form factor and at per/drive price points substantially better than standard single density enclosures. The iBOD-S supports SAS and SATA drive tiers. The dual density two-drive carrier provides front access hot swap insertion and removal of the disk drives and allows a compact high-density footprint. A range of drive carriers is available to support dual SAS, as well as single or optional dual channel access to single channel SATA drives. High efficiency single voltage power system and auto regulating variable speed fans provide quiet economical operation in a broad range of physical environments. Using cableless design and hot swap components throughout increases reliability and ease of service. Web r command line configuration, monitoring and management ease integration with controllers and subsystems.

The MPSTOR iBOD enclosure is designed specifically for OEMs looking to deploy demanding Network Storage applications including, Enterprise Data Center, Data Streaming & Video, Disk to Disk Back-up, Disaster Management, and ILM/IIM .

People in Partnership have the Edge

Copyright © 2006 MPSTOR Ltd. All rights reserved. MPSTOR, the MPSTOR logo, iBOD, and Cool By Design are trademarks of MPSTOR Ltd., which may be registered in some jurisdictions. All other trademarks used are owned by their respective owners.

Information supplied by MPSTOR Ltd. is believed to be accurate and reliable at the time of printing, but MPSTOR Ltd. assumes no responsibility for any errors that may appear in this document. MPSTOR Ltd. reserves the right, without notice, to make changes in product design or specification. Information is subject to change without notice.



iBOD-S Enclosure Specifications



Feature Description

General

4U 48 Drive High Density	Y
Front Access Hot Swap Drives	Y
Dual Drive Brick Carriers	Y
Mix and Match SAS & SATA II	Y
Cables Design	Y

Performance

Maximum Throughput Per Channel	
SAS	12 Gb/sec
SATA II	12 Gb/sec

Maximum Aggregate Throughput

SAS	48 Gb/sec
SATA II	48 Gb/sec

External Interfaces

Number of Hot Swap Interface Controllers	2
--	---

Number of Host/ External Ports

SAS	4
-----	---

Number of Host/ External Channels

SAS	16x arrow or 4x wide
-----	-------------------------

Protocols

SAS-STP-SMP-SES

Maximum Host Connections

SAS	4
-----	---

Number of Drive/ Expansion Channels

SAS	2
-----	---

Internal Capacities Per Enclosure

Maximum number of Disk Drives

SAS	48
SATA II	48
Mix Drive Types	Y
Drive Spanning	Y
Drive Brick Mirroring	Y

Hot Swap & Redundancy

Disk Drives	Y
External Interface Controllers Including Ethernet Management Port	Y
Cooling	Y
Power	Y

Feature Description

Administration

Ethernet Port	Y
Web HTTP interface	Y
Tri-Color LED Indicators	Y
Serial Port	Y
Command Line Interface	Y
Email Notification	Y
SMP	Y
SES	Y
Phone Home/ Weblink Support	Y

Alerts

Drive Failure	Y
Temperature	Y
PSU	Y
Cooling Fan	Y

Electrical & Environmental

Power Supply 450W Single Rail	Y
Universal A/C Input	90-220VAC
Operating Environment	40F-120F Non-condensing
Non-operating Environment	40F-140F Non-condensing

Enclosure Dimensions

19" EIA Rack Mount in /mm	19 / 483
4U Rack units in/ cm	7.5 /19
Depth in/cm	24 / 61
Weight excl. Drives lbs /kg	77 /35

Regulatory

Emmissions	FCC B/ CE
Safety	UL/ CE
RoHS	Y
ISO 9000 2000	Y

Copyright © 2006 MPSTOR Ltd. All rights reserved. MPSTOR, the MPSTOR logo, iBOD, and Cool By Design are trademarks of MPSTOR Ltd., which may be registered in some jurisdictions. All other trademarks used are owned by their respective owners.

Information supplied by MPSTOR Ltd. is believed to be accurate and reliable at the time of printing, but MPSTOR Ltd. assumes no responsibility for any errors that may appear in this document. MPSTOR Ltd. reserves the right, without notice, to make changes in product design or specification. Information is subject to change without notice.